

PVC Suction & Discharge Hose



Product Datasheet



Technical Specification

1. Description

PVC Spiral Light Duty Delivery and Vacuum Hose.

2. Applications:

Delivery and light duty suction of water, slurry and dilute chemicals, bilge pumps, portable pumps, crop spraying and slurry injection.

3. Tube

PVC

4. Cover

PVC

5. Reinforcement

Rigid PVC spiral

6. Temperature

-15 Deg C to +65 Deg C

7. Vacuum

570 Hg = 75% at 20°C

8. Coil Size

30 mtrs (cut lengths: 6 mtrs or multiples of 6 mtrs)

9. Colour

Translucent Green

Inside Diameter (mm)	Inside Diameter (inch)	Wall Thickness (mm)	Outside Diameter (mm)	Maximum working Pressure (23°C ± 2°C) (55°C ± 2°C)		Bend Radius (mm)	Weight (kg's/mtr)	CMT Part Number
19	3/4	3.30	25.6	5.6 bar	1.6 bar	55	0.30	0305010
25	1	3.30	31.6	5.6 bar	1.6 bar	100	0.38	0305015
32	1 ¼	3.43	38.9	4.0 bar	1.3 bar	115	0.49	0305020
38	1 ½	3.56	45.1	4.0 bar	1.3 bar	150	0.60	0305025
51	2	4.32	59.6	4.0 bar	1.3 bar	225	0.96	0305030
63	2 ½	4.57	72.1	4.0 bar	1.3 bar	240	1.25	0305035
76	3	5.08	86.2	3.0 bar	1.0 bar	265	1.63	0305040
102	4	5.84	113.7	2.3 bar	0.8 bar	330	2.52	0305045

