

Product Datasheet



Technical Specification

1. Description

Heavy Duty Rubber Coated Canvas Ducting.

2. Applications:

Traditional heavy duty industrial ducting for air, dust, fume and particle extraction. Durable, robust and extremely flexible.

3. Tube

Neoprene coated cotton fabric

4. Cover

Neoprene coated cotton fabric

5. Reinforcement

Spring steel helix

6. Temperature

-20 Deg C to +100 Deg C

7. Coil Size

6 mtrs

8. Colour

Black with Yellow stripe

Inside Diameter		Outside Diameter		Working Pressure		Burst Pressure		Coil Length		Bend Radius	Weight	CMT Part Number
(mm)	(inch)	(mm)	(inch)	(psi)	(bar)	(psi)	(bar)	(mtr)	(ft)	(mm)	(kg's/mtr)	
38	1 ½	-	-	-	-	-	-	6.0	-	50	0.65	0530003
44	1 ¾	-	-	-	-	-	-	6.0	-	65	0.45	0550004
51	2	-	-	-	-	-	-	6.0	-	65	0.70	0530005
57	2 ¼	-	-	-	-	-	-	6.0	-	75	0.90	0530010
63	2 ½	-	-	-	-	-	-	6.0	-	75	1.00	0530015
76	3	-	-	-	-	-	-	6.0	-	100	1.10	0530025
82	3 ¼	-	-	-	-	-	-	6.0	-	115	1.30	0530030
90	3 ½	-	-	-	-	-	-	6.0	-	115	1.30	0530035
102	4	-	-	-	-	-	-	6.0	-	125	1.90	0530040
115	4 ½	-	-	-	-	-	-	6.0	-	125	2.30	0530045
127	5	-	-	-	-	-	-	6.0	-	150	2.60	0530050
152	6	-	-	-	-	-	-	6.0	-	180	3.20	0530060
180	7	-	-	-	-	-	-	6.0	-	230	3.70	0530070
203	8	-	-	-	-	-	-	6.0	-	250	4.80	0530075
225	9	-	-	-	-	-	-	6.0	-	280	5.40	0530080
254	10	-	-	-	-	-	-	6.0	-	300	6.60	0530085
305	12	-	-	-	-	-	-	6.0	-	350	9.70	0530090