

Glasflex Ducting

Heating & Ventilation Flexible Ducting

Product Datasheet



Technical Specification

1. Description

Lightweight Heating and Ventilation Ducting (Compressible)
BS476 parts 6,7 and 20.

2. Applications:

Flexible connections between grills, fans and main duct work in heating and ventilation. Lightweight and extremely flexible.

3. Tube

PVC coated glass fibre fabric

4. Cover

PVC coated glass fibre fabric

5. Reinforcement

High tensile spring steel helix

6. Temperature

-20 Deg C to +70 Deg C

7. Coil Size

6 mtrs

8. Colour

Grey

Inside Diameter (mm)	Inside Diameter (inch)	Outside Diameter (mm)	Outside Diameter (inch)	Working Pressure (psi)	Working Pressure (Pa)	Burst Pressure (psi)	Burst Pressure (bar)	Vacuum HG (mtr)	Vacuum HG (inch)	Inside Bend Radius (mm)	Weight (kg's/mtr)	CMT Part Number
80	-	-	-	0.36	2500	-	-	-	-	38	0.355	0504015
100	-	-	-	0.36	2500	-	-	-	-	51	0.445	0504030
114	-	-	-	0.36	2500	-	-	-	-	58	0.495	0504035
125	-	-	-	0.36	2500	-	-	-	-	64	0.540	0504045
150	-	-	-	0.36	2500	-	-	-	-	76	0.655	0504055
160	-	-	-	0.36	2500	-	-	-	-	80	0.690	0504060
180	-	-	-	0.36	2500	-	-	-	-	89	0.800	0504070
200	-	-	-	0.36	2500	-	-	-	-	101	0.910	0504075
224	-	-	-	0.36	2500	-	-	-	-	114	1.145	0504080
250	-	-	-	0.36	2500	-	-	-	-	127	1.270	0504085
300	-	-	-	0.36	2500	-	-	-	-	152	1.525	0504095
355	-	-	-	0.36	2500	-	-	-	-	178	1.200	0504105
400	-	-	-	0.36	2500	-	-	-	-	203	1.500	0504110
450	-	-	-	0.36	2500	-	-	-	-	229	1.600	0504115
500	-	-	-	0.36	2500	-	-	-	-	254	1.700	0504120
560	-	-	-	0.36	2500	-	-	-	-	279	1.800	0504125
600	-	-	-	0.36	2500	-	-	-	-	305	2.000	0504130