

Layflat Delivery Hose

Product Datasheet



Technical Specification

1. Description

Medium Duty PVC Layflat Hose.

2. Applications:

Discharge of water from portable, mobile or static pumps in construction, mining and agriculture. Hose has an increased wall thickness for longer life.

3. Tube

PVC

4. Cover

PVC

5. Reinforcement

Synthetic Yarn

6. Temperature

-10 Deg C to +66 Deg C

7. Working Pressure Temperature:

Rated at 23°C +/- 2°C

8. Coil Size

91.5 mtrs (cut lengths: 30.5 mtrs or multiples of 30.5 mtrs)

9. Colour

Blue

Inside Diameter		Outside Diameter		Working Pressure		Burst Pressure		Vacuum HG		Bend Radius	Weight	CMT Part Number
(mm)	(inch)	(mm)	(inch)	(psi)	(bar)	(psi)	(bar)	(mm)	(inch)	(mm)	(kg's/mtr)	
38.10	1 ½	42.42	1.67	90	6	270	18.0	-	-	-	0.3	0347005
50.80	2	56.13	2.21	80	5	240	15.0	-	-	-	0.42	0347010
63.50	2 ½	68.07	2.68	55	3.7	165	11.1	-	-	-	0.46	0347015
76.20	3	81.28	3.2	55	3.7	165	11.1	-	-	-	0.58	0347020
101.60	4	108.2	4.26	50	3	150	9.0	-	-	-	0.82	0347025
152.40	6	159.0	6.26	35	2.3	105	6.9	-	-	-	1.31	0347030
203.2	8	211.3	8.32	35	2.3	105	6.9	-	-	-	1.93	0347035