

PVC Layflat Delivery Hose

Product Datasheet



Technical Specification

1. Description

Heavy Duty PVC Layflat. Hose Flame Resistant: USMSHA 2G-14/16.

2. Applications:

Discharge of water where higher pressure is required. Hose has increased wall thickness for extra durability.

3. Tube

PVC

4. Cover

PVC

5. Reinforcement

Synthetic Yarn

6. Temperature

-10 Deg C to +66 Deg C

7. Working Pressure Temperature:

Rated at 23°C +/- 2°C

8. Coil Size

91.5 mtrs (cut lengths: 30.5 mtrs or multiples of 30.5 mtrs)

9. Colour

Red

Inside Diameter		Outside Diameter		Working Pressure		Burst Pressure		Vacuum HG		Bend Radius	Weight	CMT Part Number
(mm)	(inch)	(mm)	(inch)	(psi)	(bar)	(psi)	(bar)	(mm)	(inch)	(mm)	(kg's/mtr)	
50.80	2	56.9	2.24	150	10	450	30	-	-	-	0.54	0350010
76.20	3	83.57	3.29	125	8	375	24	-	-	-	0.68	0350020
101.60	4	109.73	4.32	100	6	300	18	-	-	-	1.09	0350025
152.40	6	162.56	6.4	100	6	300	18	-	-	-	1.76	0350030